



41 Wellman St., Lowell, MA 01851 USA  
 www.galvanic.com email: info@galvanic.com

Tel: 978-848-2701  
 Fax: 978-848-2713

**APPLICATION DATA COLLECTION SHEET for Nametre Products – Viscosity**

CLIENT:		Date:	
Company			
Plant:		Process/Line:	
Contact Name:		Title:	
Address:			
City:	State:	Zip:	Country:
Phone:		Fax:	
email:		Web address: http://	

Material: \_\_\_\_\_

Viscosity range: Maximum \_\_\_\_\_ Minimum \_\_\_\_\_

Temperature Range: Maximum \_\_\_\_\_ Minimum \_\_\_\_\_

Pressure range: Maximum \_\_\_\_\_ Minimum \_\_\_\_\_

Presence of solids: Yes \_\_\_\_\_ No \_\_\_\_\_ If present, the % is: \_\_\_\_\_

Installation in : Tank \_\_\_\_\_ Pipeline \_\_\_\_\_ Other: \_\_\_\_\_

Type of installation: Flange \_\_\_\_\_ Screw \_\_\_\_\_ Clamp \_\_\_\_\_ Other: \_\_\_\_\_

If tank installation: Propeller \_\_\_\_\_ Blade \_\_\_\_\_ Other: \_\_\_\_\_

Agitator speed: \_\_\_\_\_ Tank capacity: \_\_\_\_\_

If pipeline installation: Flow rate \_\_\_\_\_ Pipe I.D.: \_\_\_\_\_

Outputs required: 4-20 mA Relays \_\_\_\_\_ RS-232 \_\_\_\_\_

Distance between controller and sensor \_\_\_\_\_ feet \_\_\_\_\_ meters \_\_\_\_\_

Is material dangerous? Yes \_\_\_ No \_\_\_ Why (erosive/flammable/explosive/other)?: \_\_\_\_\_

Hazardous classification: Sensor \_\_\_\_\_ Electronics \_\_\_\_\_

Power supply: 110VAC \_\_\_\_\_ 220VAC \_\_\_\_\_ Phases: \_\_\_\_\_

Multiplex option required (up to four sensors/transducers): Yes \_\_\_\_\_ No \_\_\_\_\_

Special comments about process: \_\_\_\_\_

Return this form to the sales person you are working with, or to:

Fred Meyer, Product Manager - Email: fmeyer@galvanic.com  
 Tel: 978-848-2701 ext 263 Fax: 978-848-2713