

GASMICRO SPECIFICATIONS

PERFORMANCE

| | |
|---|---|
| Accuracy @ 25°C (77° F) | Corrected volume: +/- 0.05% of reading Pressure: +/- 0.05% of reading Temperature: +/- 0.14°C (+/- 0.25°F) |
| Accuracy over -40°C to 65°C (-40°F to 149°F) | Corrected volume: +/- 0.2% of reading Pressure: +/- 0.2% of reading Temperature: +/- 0.5°C (+/- 0.9°F) |
| Initial Reverification Period (Measurement Canada) | 12 years |

ENVIRONMENT

| | |
|----------------------------|--|
| Ambient temperature | -40°C to 65°C (-40°F to 149°F) |
| Dimensions | 195 mm W x 310 mm H x 135 mm D (7.7" W x 12.2" H x 5.3" D) |
| Weight | 4.5 kg (10 lbs) |

UTILITIES

| | |
|--------------------------------|--|
| Power & consumption | Battery operated (6 D-cell) 4-year battery life |
|--------------------------------|--|

COMMUNICATIONS

| | |
|------------------------|--|
| Digital Outputs | Modbus RS232, dial-up and wireless modem |
| Pulse Outputs | 2 |

APPROVALS & CERTIFICATIONS

CSA, Class 1 Division 1, Groups C,D
Measurement Canada for Custody Transfer